UNIMAT V OVERLAP

Microprocessor-controlled high-performance tool for overlap welding of industrial fabrics with hot air.

- High welding speed
- User-friendly
- Digital display of set and actual values of welding speed, temperature and air flow
- No corrective action required thanks to the new guide roller
- Steplessly controlled air flow
- Wrinkle-free welding
- Automatic start
- Integrated liftig mechanism



SPECIFICATIONS

UNIMAT Überlapp 230 V

Voltage	V~	230
Power consumption	W	3680
Frequency	Hz	50 / 60
Temperature	°C	20 - 620
Speed	m/min	1.5 - 12
Air flow (20°C)	l/min	500
Air flow range	%	50 - 100
Pressure static	Pa	max. 5000 (50 mbar)
Noise emission level LpA	dB	70
Welding nozzle with	mm	20 or 40
Size (L x W x H)	mm	600 x 430 x 310
Weight	kg	23.0 (with 5 m cord)
Marking of conformity		CE
Approval mark		

Leister Process Technologies
Riedstrasse
CH-6060 Sarnen/Switzerland
Phone: +41 41 662 74 74
Fax: +41 41 662 74 16
sales@leister.com

Certification scheme	CCA
Protection class I	

ACCESSORIES



Retrofit kit OVERLAPP

115.184 - Retrofit kit OVERLAP 20 mm
115.185 - Retrofit kit OVERLAP 40 mm from TAPE to OVERLAP

Andrückrolle 20 mm / 40 mm Keder with ball bearings

117.308 - Pressure roller 20 mm piping, with ball bearings
117.314 - Pressure roller 40 mm piping, with ball bearings

Leister Process Technologies
Riedstrasse
CH-6060 Sarnen/Switzerland
Phone: +41 41 662 74 74
Fax: +41 41 662 74 16
sales@leister.com